



NUMERIC MESSAGING
ONE WAY PAGER
NP-30

Great Things Come From Small Packages



Unication Numeric Pager

The NP-30 is a top-view numeric pager that combines multifunction with your daily activities, no matter personal life or business field. You can apply NP-30 for every aspect only based on easy operation mode. With the powerful function of auto-save message when off and changing the battery, you won't miss any important message.

To have Unication NP-30 numeric pager will lead your life to convenient field.

NUMERIC PAGER

Model Type

NP-30 Numeric Tone Pager POCSAG

Synthesized

NP-30

Product Specifications

	VHF	UHF
Frequency Range	143-153 MHz / 153-163 MHz 163-174 MHz / 276-284 MHz	450-460 MHz / 450-460 MHz
Transmission Speed	512 / 1200 / 2400 bps	512 / 1200 / 2400 bps
Protocol	POCSAG	POCSAG
Paging Sensitivity (uV/m)	Baud 512 : $\leq 5\mu\text{V/m}$ Baud 1200 : $\leq 7\mu\text{V/m}$ Baud 2400 : $\leq 9\mu\text{V/m}$	Baud 512 : $\leq 5\mu\text{V/m}$ Baud 1200 : $\leq 7\mu\text{V/m}$ Baud 2400 : $\leq 9\mu\text{V/m}$
Modulation	FSK+/-4.5 KHz	FSK+/-4.5 KHz
Channel Width	12.5 KHz	12.5 KHz
Intermediate Frequency	21.4 MHz / 455 MHz	21.4 MHz / 455 MHz
Adjacent Channel Selectivity	55dB@+/-25 KHz	55dB@+/-25 KHz
Image Frequency Rejection	40dB	40dB
Spurious Response Rejection	40dB	40dB
Intermodulation Rejection	50dB	50dB
Alert Response	75dB@30cm	75dB@30cm
Ambient Working Temperature	-10~55°C	-10~55°C
Battery	1.5 Volt AA Alkaline x 1	1.5 Volt AA Alkaline x 1
Dimension	(L) 68mm x (W) 50mm x (H) 18mm	(L) 68mm x (W) 50mm x (H) 18mm

NP-30 Feature List

- * Six Cap Codes (Address)
- * 16 Message Slots
- * Capacity : LCD 12 Digits & 4 ICON
- * Message Display on LCD
- * Message Time Stamping
- * Message Full Indication
- * Selective Erase \ Erase All
- * Save Message When Off & Changing the Battery
- * Backlight Display
- * Full Function Self Test
- * Unread Message Indication
- * Out of Range Indication
- * Low Battery Alert & Indication
- * Program by RS232

For more information, please contact



Unication

©2011 Unication CO., LTD.
The information contained in this document is the exclusive property of Unication CO., LTD.
It shall not be disclosed, distributed or reproduced in whole or in part without written permission of Unication CO., LTD.

Head Office
Unication CO., Ltd.
Tel.: +886-2-2299-9678
Address: 5F., No.6, Wu-Kung 5Rd.,
Hsinchuang District, New Taipei City, Taiwan
Email: salesenquiry@uni.com.tw

North America Branch Office
Unication USA Inc.
Tel.: +1-817-303-9320
Address: 1901 E. Lamar Blvd.,
Arlington, TX 76006, U.S.A.
Email: sales@unication.com