



When you serve to save lives



ALPHA ELEGANT
We serve you to save lives



Unication

anytime anywhere for services: +medical +emergency +security +hospitality +entertainment etc.

www.unication.com

ALPHR ELEGANT features

DISPLAY

A whole new Alphanumeric Pager, Alpha Legend+ comes with display flexibility. Customize your own pager display to suit your daily operations.

- 4 Line / 2 Line Text Zooming
- Programmable Default Zooming
- 20 Alphanumeric Characters per Line
- EL Backlight and Brightness Sensor for Auto Backlight
- Time and Date Display (Format Programmable)

ALERT

A variety of alerting modes can be assigned to each address.

- Aler Tone Programmed Via PPS or Front Panel
- Reminder Alert Tone Selectable
- Louder Alert SPL ≤ 80 dB at 12 inch
- 7 Alert modes selectable (Standard Alert, Escalating Alert, Vibrating, Intermittent Vibrate, Vibrating & Alert, Vibrating then Alert, Chirp and Silent)
- 16 Audio Alerts and 2 Vibrating Alerts (Normal and Intermittent)
- Expanded Alerting Options for Maildrop

INDICATORS

A variety of Audio and icon indicators provide status information for :

- Unread Messages, Out of Range, Battery, Memory Full, Alarm Clock, Private Time On, On / Off Duty Indicator, Alert Mode Indicator



MESSAGING

- 8 RIC (32 sub-addresses)
- On/ Off Duty Receiving Mode
- Total 32 KB Message Memory Capacity
- Duplicate Message Detection
- Important Message Lock
- Notebook Entries
- Message Preview, Time & Date Stamping, Alarm
- Auto On / Off
- Up to 2025 characters for 1 Personal Message
- Up to 5052 characters for 1 Personal Message

specifications

	Wide Band		
	VHF	UHF	900MHz
Frequency Range	137-143 MHz 143-153 MHz 152-164 MHz 163-174 MHz	450-460 MHz 460-470 MHz	929-932 MHz
Baud Rate	512 / 1200 / 2400		
Code Format	POCSAG (CIR No.1 NRZ FSK)		
Paging Sensitivity (uV/m)	Baud 512 : ≤ 5.7 / Baud 1200 : ≤ 8 / Baud 2400 : ≤ 10.3		
Selectivity	≥ 60 dB	≥ 55 dB	≥ 50 dB
Spurious & Image Rejection	≥ 50 dB		≥ 40 dB
High Level Intermodulation	+3 dB > 50 dB		+3 dB > 40 dB
Frequency Stability	$\leq \pm 15$ ppm	$\leq \pm 5$ ppm	$\leq \pm 3.5$ ppm
Channel Spacing	25 KHz		
Receiver Type	Synthesized		
Address Capability	Elegant : 8 RIC (32 Subaddresses)		
Frequency Deviation	± 4.5 KHz		
Alert Tone SPL	> 80 dB @ 12 inches (2730 Hz Standard Alert)		
Operating Temperature	+5° to +40°C		
Storage Temperature	-40° to +85°C		
Power Supply	Single AA Alkaline Battery, 1.5 V		
Battery Life*	Baud 512 : 62 days / Baud 1200 : 54 days / Baud 2400 : 45 days		
Low Battery Alert Level	1.24 Volts (Programmable)		
Weight with Battery	87.5g (3.1 oz)		
Dimension	81.0 X 55.0 X 18.5 mm (3.19" X 2.16" X 0.73")		

* Estimated battery life is based on full batter capacity and 2 pages per day.



Unication

Head Office
Unication CO., Ltd.
Tel.: +886-2-2299-9678
Address: 5F, No.6, Wu-Kung 5Rd.,
Hsinchuang District, New Taipei City, Taiwan
Email: salesenquiry@uni.com.tw

North America Branch Office
Unication USA Inc.
Tel.: +1-817-303-9320
Address: 1901 E. Lamar Blvd.,
Arlington, TX 76006, U.S.A.
Email: sales@unication.com



Class I, Division II, Group A, B, C, D
Class II, Division II, Group F, G
Class I, Division I, Group C, D (Optional)